

Impact-Resistant Entrances

High Velocity Hurricane Zone (HVHZ) Applications

Series 281 Narrow Stile Impact-Resistant Entrances (Wet-Glazed)

Qualified System Configuration Chart

Design Pressure	Maximum Door Size		Maximum Glass Size		Qualified Glass Types				
P.S.F.	Single	Double	D.L.O. (WxH)	Sq. Ft.	Glass Types				
Series 281 Narrow Stile - Large Missle									
+65/-65	36 x 84	72 x 84	29%6" x 71 %6"	14.7	В				

Hurricane Impact-Resistant Products Disclaimer Note

Coral's hurricane impact-resistant products meet a variety of test standards for applications in coastal construction regions satisfying the demands for wind-borne debris hazards and high-velocity winds associated with hurricanes. All of Coral's hurricane impact-resistant products are independent laboratory tested based on a variety of test standards for air infiltration, structural loads, missile impact and air-pressure cycling based on ASTM and/or Florida Building Code. The informational chart above is intended to provide recommended limits in frame heights, glass sizes and design pressures based on product testing. When exceeding conditions listed above, it is recommended to consult with a licensed structural engineer or contact Coral Architectural Products.

Hardware Applications

	• •						
Locking and Closer Options							
Active Leaf	DH072 3-Point Lock with DH078 Cylinder and DH079 Thumbturn						
Inactive Leaf	DH176 Steel Tip Flush Bolts (2 each)						
Surface Applied Closer	Heavy Duty ANSI Grade 1 (Required)						
Concealed Overhead Closer	ANSI Grade 1 (Required)						
Hinging Options							
Туре	Description	Quantity					
Butt Hinges	DH110SS (Stainless Steel) 4½" x 4"	1½ Pairs					
Continuous Geared Hinge	DH111HD (Heavy Duty)	Full Door Height					
Panic Exit Devices Options							
Jackson	2086-HR ANSI Grade 1	Concealed Vertical Rod					

Qualified Glass Types

	Glass Type	Glass Composition			Interlayer	Glass
		Exterior Lite	Interlayer	Interior Lite	Manufacturer	Identification
	%°" Monolithic Glass	1/4" Heat Strengthened Glass	.090 Saflex PVB Interlayer	¼" Heat Strengthened Glass	Solutia	В