


All Glass Storefront Work Sheet



	F	in	is	h
--	---	----	----	---

<u>Finish</u>
Clear Anodized US28
Dark Bronze Anodized
Polished Stainless Steel Clad US32
Brushed Stainless Steel Clad US32D
Polished Brass Clad US3N
Other

Glass Thickness:

Glass Type:

1/2"
Clear

BP

3/8"

	3/4'

Bronze Grey

Satin Etch	
------------	--

Other

ABOVE DOOR

Aluminum Header 1-3/4 x 4-1/2" Header

Recessed Header Yes No

Overhead Concealed Closer*

- 105 Deg No Hold Open OHCC
- 90 Deg No Hold Open OHCC
- 105 Deg Hold Open OHCC
- 90 Deg Hold Open OHCC

*(Pivot hardware included with closer)

BELOW DOOR

Concealed Floor Closer*

- 105 Deg No Hold Open Floor
- 90 Deg No Hold Open Floor
- 105 Deg Hold Open Floor
- 90 Deg Hold Open Floor

1/2" Threshold

4"

Top

Full Length Rail

DOOR RAILS/PATCHES

- 4" Square Rail
- 4" Tapered Rail
- 6" Square Rail
- 10" Square Rail

Door Patch

- Square 4" x 9-1/2"
- Tapered 4" x 9-1/2"
- Patch Fitting 2" x 6-7/16"

Bottom

Full Length Rail

- 4" Square Rail
- 4" Tapered Rail
- 6" Square Rail
- 10" Square Rail

Door Patch

- Square 4" x 9-1/2"
- Tapered 4" x 9-1/2"
- Patch Fitting 2" x 6-7/16"

SYSTEM OPTIONS

Side Lites

(Top)

- U-Channel
- 4"Square Rail
- 4" Tapered Rail
- 6" Square Rail
- 10" Square Rail

(Bottom)

- U-Channel
- 4"Square Rail
- 4" Tapered Rail
- 6" Square Rail
- 10" Square Rail

Locks

Position

Bottom:	Yes	∐No
Cantar.	□Voc	

Style

Inside: Thumbturn Keyed Cylinder Outside: Keyed Cylinder

INFORMATION

COMPANY: CONTACT: PHONE **FAX NUMBER:** EMAIL: JOB NAME:

Push/Pull

Style: Size: Finish:



All Glass Storefront Work Sheet

These Elevations Are Representative Of Many CAP All Glass System Configurations.

