

**DADE COUNTY APPLICATIONS
OPTIONS AND LIMITATIONS****SERIES 381 MEDIUM STILE DOORS FOR LARGE MISSILE IMPACT
(NOA PENDING)**

DESIGN PRESSURE P.S.F.	MAXIMUM DOOR SIZE		MAXIMUM GLASS SIZE		QUALIFIED GLASS TYPES
	SINGLE	PAIR	D.L.O. W X H	SQ. FT.	
+70/-80	42" X 96"	84" X 96"	32 5/16" X 81 11/16"	18.3	B & U

LOCKING AND CLOSER OPTIONS

ACTIVE LEAF	DH072 3-POINT LOCK WITH DH078 CYLINDER & DH079 THUMBTURN
INACTIVE LEAF	2 EA. DH176 STEEL TIP FLUSH BOLTS.
SURFACE	HEAVY DUTY ANSI GRADE 1 CLOSER
C.O.C.	JACKSON ANSI GRADE 1 OR EQUAL

HINGING OPTIONS

TYPE	DESCRIPTION	QUANTITY
BUTTS	DH109 4 1/2" X 4"	1 1/2 PAIR

PANIC EXIT DEVICES OPTIONS

MANUFACTURER	SERIES	TYPE
JACKSON CORPORATION	2086 HR ANSI GRADE 1	CONCEALED VERTICAL ROD

GLASS COMPOSITION	MANUFACTURER	GLASS TYPE
9/16" LAMINATED GLASS CONSISTING OF TWO 1/4" HS GLASS LITES AND 0.090 SOLUTIA SAFLEX PVB INTERLAYER. NOA #03-0105.02	SOLUTIA	B
9/16" LAMINATED GLASS CONSISTING OF TWO 1/4" HS GLASS LITES AND 0.120 UVEKOL INTERLAYER. NOA #03-1117.05	CORAL INDUSTRIES, INC.	U