

DADE COUNTY APPLICATIONS OPTIONS AND LIMITATIONS

SERIES 281 NARROW STILE DOORS FOR LARGE MISSILE IMPACT (NOA PENDING)

DESIGN PRESSURE P.S.F.	MAXIMUM DOOR SIZE		MAXIMUM GLASS SIZE		QUALIFIED GLASS TYPES
	SINGLE	PAIR	D.L.O. W X H	SQ. FT.	
+65/-65	36" X 84"	72" X 84"	29 9/16" X 71 7/16"	14.7	B & U

LOCKING AND CLOSER OPTIONS

ACTIVE LEAF	DH072 3-POINT LOCK WITH DH078 CYLINDER & DH079 THUMBTURN
INACTIVE LEAF	2 EA. DH176 STEEL TIP FLUSH BOLTS.
SURFACE	HEAVY DUTY ANSI GRADE 1 CLOSER
C.O.C.	JACKSON ANSI GRADE 1 OR EQUAL

HINGING OPTIONS

TYPE	DESCRIPTION	QUANTITY
BUTTS	DH109 4 1/2" X 4"	1 1/2 PAIR

PANIC EXIT DEVICES OPTIONS

MANUFACTURER	SERIES	TYPE
JACKSON CORPORATION	2086 HR ANSI GRADE 1	CONCEALED VERTICAL ROD

GLASS COMPOSITION	MANUFACTURER	GLASS TYPE
9/16" LAMINATED GLASS CONSISTING OF TWO 1/4" HS GLASS LITES AND 0.090 SOLUTIA SAFLEX PVB INTERLAYER. NOA #03-0105.02	SOLUTIA	B
9/16" LAMINATED GLASS CONSISTING OF TWO 1/4" HS GLASS LITES AND 0.120 UVEKOL INTERLAYER. NOA #03-1117.05	CORAL INDUSTRIES, INC.	U